

Declaration of Performance

No. 002DoP-FAE-BIIa

- 1: Unique identification of product type: Dry pressed ceramic tiles with water absorption $3\% < E_b \le 6\%$
- 2: Intended use(s): For internal walls and floorings
- 3: Name and contact address of the manufacturer: Ceramica Faetano S.p.a. –Strada del Marano, 24 47896 Faetano – Repubblica di San Marino
- 4: AVCP: Systems 4
- 5: Name and identification number of notified laboratory: **not applicable**
- 6: Declared performances

Essential characteristics	<u>Performance</u>	Harmonized technical specification
Reaction to fire	$A1$ - $A1_{FL}$	
Release of dangerous substance, for:		
Cadmium	NPD	EN 14411:2012
Lead	NPD	
Breaking strength thickness > 7.5mm	>1000 N	
thickness < 7.5mm	>600 N	
Slipperiness	NPD	
Tactility	NPD	
Bond/Strength adhesion, for:		
Cementitious adhesive, type C2	1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
Internal use:	Pass	
External use: (freeze/thaw resistance)	NPD	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: Ing. Giuseppe Ferri Technical Director

Place and date of issue

Signature

Faetano 27/06/2013

REP. SAN MARINO - C.O.E. SM 00308