

	SERIE	DIN 51130	DIN 51097	ASTM C1028		BCRA	
				dry	wet	dry	wet
STONE	AYERS ROCK	R12	A+B+C	≥0,90	≥0,60	≥0,80	≥0,70
	BORGHI D'ITALIA 15x30	R11	npd	≥0,80	≥0,60	npd	npd
	BORGHI D'ITALIA 30x30	R11	npd	≥0,80	≥0,60	npd	npd
	BORGHI D'ITALIA 60x60	R9	npd	≥0,80	≥0,60	npd	npd
	COUNTRY LIFE	R10	A+B	≥0,70	≥0,70	≥0,40	≥0,50
	COVENT GARDEN	R9	npd	≥0,70	≥0,60	npd	npd
	DUOMO	R10	npd	≥0,80	≥0,60	npd	npd
	HIMALAYA	R10	npd	≥0,80	≥0,70	npd	npd
	LITHOS	R10	npd	npd	npd	npd	npd
	LOFT	R10	A+B+C	≥0,70	≥0,70	≥0,80	≥0,60
	MANHATTAN	R9	npd	≥0,80	≥0,60	≥0,50	≥0,40
	MARFIL	npd	npd	npd	npd	npd	npd
	OPERA	R9	npd	≥0,60	≥0,60	npd	npd
	PIERRE ROYALE	R9	B	≥0,80	≥0,60	≥0,50	≥0,70
	PIERRE ROYALE grip	R12	npd	npd	npd	npd	npd
	PROGETTO 8.4	R9	npd	≥0,80	≥0,60	npd	npd
	QUARZ DESIGN	R10	npd	≥0,70	≥0,60	npd	npd
	QUARZ DESIGN 20mm	R12	A+B+C	≥0,90	≥0,80	≥0,90	≥0,90
	TAYLORMADE	R9	A+B	≥0,80	≥0,60	≥0,80	≥0,70
	TREND	R10	npd	≥0,70	≥0,60	npd	npd
VIEW 360	R10	A+B	≥0,90	≥0,60	≥0,70	≥0,60	
VIEW 360 grip	R12	A+B+C	npd	npd	npd	npd	
VILLA IMPERIALE	R10	A	npd	npd	≥0,60	≥0,50	
WOODSHED	R10	npd	npd	npd	npd	npd	
LE PORCELLANE SMALTATE	AMALFI	npd	npd	npd	npd	npd	npd
	ANTICHE DOGHE	R10	A	≥0,80	≥0,60	≥0,70	≥0,50
	CAVE DEL PANARO	R10	npd	npd	npd	npd	npd
	MARMI ANTICHI	npd	npd	npd	npd	npd	npd
	TERRE SENESI	R9	npd	npd	npd	npd	npd
PROGETTO	TRADIZIONALE	npd	npd	npd	npd	npd	npd
HABITAT	TAYLORMADE	npd	npd	npd	npd	npd	npd
	BORGHI D'ITALIA	npd	npd	npd	npd	npd	npd

Declaration of Performance

No. 001DoP-PST-BIa

1: Unique identification code of the product type : Dry-Pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$.

2: Intended use : For internal and external walls and floorings.

3: Name or registered trade mark, and contact address of the manufacturer : Pastorelli S.p.a. - Via Magazzino 1944 - 41056 Savignano S/P - Mo -Italy.

4: System of assessment and verification of constancy of performance (AVCP) : 4

5: Name and identification number of notified laboratory, if relevant: not applicable

6: Declared performance :

<u>Essential Characteristics</u>	<u>Performance</u>	<u>Harmonized Technical Specification</u>
Reaction to fire	$A1 - A1_{FL}$	EN 14411:2012
Release of dangerous substance, for		
Cadmium	NPD	
Lead	NPD	
Breaking Strength:	$> 1300 N$	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion for:		
Cementitious adhesive, type C2	$1 N/mm^2$	
Thermal shock resistance	Pass	
Durability		
Internal use:	Pass	
External use: (freeze-thaw resistance)	Pass	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: Luca Costi Technical Director

Place and date of issue

Savignano S.P. 06/17/2013


 PASTORELLI SpA

This documents of performance does not include decorative accessories, trim and mosaic.